

ONE STOP SOLUTION FOR FreezerChiller



Adjustable Digital Temperature control certified by CE & UL standard.



Angular design on the base plate complies with all sanitation requirement.



Epoxy coated shelves are hard, strong and easy to clean. Tested for durability at -35 °C



environmental friendly



energy saving

UPRIGHT REFRIGERATOR

Features

- ✓ All stainless steel
- ✓ Good quality low noise compressor
- ✓ Reliable electronic temperature control and display
- ✓ Adjustable shelves for products with different height
- ✓ Available in static or ventilated cooling system
- ✓ Available as chiller or freezer

| Models | US2DF/ YBF9205 | US2DC/ YBF9204 | US2DF/ YBF9225 | US4DC/ YBF9224 | US6DF/ YBF9243 | US6DC/ YBF9235 |
|-----------------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|
| Width (mm) | 600 | 600 | 1200 | 1200 | 1800 | 1800 |
| Depth (mm) | 740 | 740 | 740 | 740 | 740 | 740 |
| Height (mm) | 1950 | 1950 | 1950 | 1950 | 1950 | 1950 |
| Compressor Power (HP) | 1/2 | 1/2 | 4/5 | 1/2 | 1/2x2 | 3/5 |
| Compressor | Danfoss | Danfoss | Danfoss | Danfoss | Danfoss | Danfoss |
| Refrigerant | R404a | R134a | R404a | R134a | R404a | R134a |
| Power (W) | 500 | 280 | 420 | 480 | 650 | 590 |
| Power Supply (V/Hz) | 230/50 | 230/50 | 230/50 | 230/50 | 230/50 | 230/50 |
| Capacity (L) | 400 | 400 | 900 | 900 | 1400 | 1400 |
| Doors | 2 | 2 | 4 | 4 | 6 | 6 |
| Shelves | 3 | 3 | 6 | 6 | 9 | 9 |
| Consumption (kwh/24h) | 4 | 4 | 6 | 6 | 8.5 | 8.5 |
| Cooling Type | Fan Assisted | Fan Assisted | Fan Assisted | Fan Assisted | Fan Assisted | Fan Assisted |
| Temperature (°C) | -6 ~ -18 | +2 ~ +10 | -6 ~ -18 | +2 ~ +10 | -6 ~ -18 | +2 ~ +10 |
| Defrost | Automatic | Automatic | Automatic | Automatic | Automatic | Automatic |
| Digital Controller | Carel | Carel | Carel | Carel | Carel | Carel |