

REACH-IN Display Chiller (Blower)



environmental friendly



energy saving

Characteristics

- ✓ Fitted light box
- ✓ Double-layer tempered glass door
- ✓ Adjustable shelves
- ✓ Adjustable feet or wheels (optional)
- ✓ Door lock



Models	RIS250C/LG-250F	RIS300C/LG-300F	RIS430C/LG-430F	RIS800C/LG-800	RIS1000C/LG-1000
Capacity					
Net (lt)	250	300	430	800	1000
Max.Ambient Temp (C)	38	38	38	38	38
Voltage/frequence	220 ~ 240V/50HZ	220 ~ 240V/50HZ	220 ~ 240V/50HZ	220 ~ 240V/50HZ	220 ~ 240V/50HZ
Features					
Cabinet Tem. C	0 ~ 10	0 ~ 10	0 ~ 10	0 ~ 10	0 ~ 10
Control/Temperature digital screen	Electronic/LED	Electronic/LED	Electronic/LED	Electronic/LED	Electronic/LED
Cooling system/Auto-Defrostt	Fan cooling/Yes	Fan cooling/Yes	Fan cooling/Yes	Fan cooling/Yes	Fan cooling/Yes
Internal light horizontal./vertical.*	Yes/Option	Yes/Option	Vertical*1	Vertical*2	Vertical*2
Door frame, door handle material	Pvc	Pvc	Pvc	Pvc	Pvc
Glass type, (low-e coated/tempered)*	Normal	Normal	Normal	tempered	tempered
Auto closing doors	For optional	For optional	For optional	For optional	For optional
Dimensions					
External Dimension W x D x H(mm)	530 x 595 x 1821	620 x 595 x 1921	620 x 690 x 2073	1000 x 730 x 2036	1200 x 730 x 2036
Certification	CE,ROHS	CE,ROHS,SASO	CE,ROHS,GS	CE,ROHS,SASO,MEPS	CE,ROHS,SASO,MEPS,GS